


Engine Replacement Guide

First, pick the shaded HP closest to the original engine.

Next, match the mounting centers for ease of installation.

Third, make sure it fits.

Last, look at the overall engine data and make the final selection based on the best match.



MODEL	MFG	HP	# CYL	MTG CENTERS	REAR MTG CTR	OVERALL LENGTH	RPM	CID	MAX TORQUE	@ RPM
7A One	W	6.4	1	12/14		25.1	3000	17.7	11.3	2590
P10	W	10	2	14.5		26.12	3000	29.4	20	2000
W 10 Two	W	10	2	15		25	3600	27.5	18	2200
11A One	W	10.7	1	18.9		23.7	3000	32	20.4	2170
M2-12	U	11	2	14.5/16		23	3600	26	19.5	2600
12C Two	W	12	2	14.5		25	3000	38.8	30	2200
W-13	W	13.5	2	14.5/16/18		26.3	3000	27	25	2500
4-60	W	15	4	13/15/18	18	37.5	2500	58	36	1800
M-15	U	11	2	11.5		25.6	3000	31	21.9	2000
W 18	W	18	3	14.5/16		28.4	3300	48	30	2400
20B Two	W	18	2	14.5		25	3600	38.8	30	2200
M3-20	U	18	3	11.5/16		25.9	3600	39	28.5	2500
P20	W	20	2	15.5		32.3	3000	58.8	40	1500
M3-20B	U	20	3	11.5/14.5/16		26.4	3600	43.8	33	2500
M-25	U	21	3	11.5/16		28.5	3200	52	40	1850
L-25	W	22	4	20/22.75		35.25	2400	97.6	58	2400
RD60	W	22	4	11.5		29.64	3000	60	57	2600
W 21	W	22	3	14.5/16		28.38	3000	60	42	2000
M-25XP	U	23	3	11.5/16		27.5	3200	57	43.8	1850
M4-30	U	25	4	11.5/16		29.1	3600	52	39	2600
M-25XPB	U	26	3	11.5/16		28.4	3000	61.2	47	2440
30B Three	W	27	3	16		28.8	3600	58	44	2150
35C Three	W	29	3	14.5/16		29.6	3600	80.4	47	2260
35D Three	W	31	3	14.5/16/18.5		31.4	3000	80.4	59	1940
W 27	W	30	3	14.5/16		32.6	3000	80	55	2600
W 30	W	30	4	16/18	18	41	3000	91	58	1800
M-35	U	30	4	11.5/16		31.8	3200	75	56	1800
M-40	U	32	4	16		35.5	2800	91	68	1600
35B Three	W	32	3	14.5/16		30.1	3600	68	41	2300
35C Three	W	29	3	14.5/16		29.6	3600	80.4	47	2260
W 33	W	33	4	16/18		34.6	3000	91	67	2100
M35B	U	35	4	11.5/16		32.7	3000	81.5	62	2460
38B Four	W	37	4	14.5/16		33.77	3600	79.6	53	2400
M-40B	U	37.5	4	11.5/16		33.2	3000	81.4	73	2180
W 40	W	40	4	16/18		40.5	3000	107	80	2250
44A Four	W	40	4	14.5/16/18.5		33.4	3600	107.2	76	1920
42B Four	W	42	4	14.5/16		33.78	3600	91	56	2500
44B Four	W	44	4	14.6/16/18.6		34.9	3000	107.2	77	2480
44A Four	W	40	4	14.5/16/18.5		33.4	3600	107.2	76	1920
42B Four	W	42	4	14.5/16		33.78	3600	91	56	2500
W 50	W	41	4	18			3200	110	85	2000
M-50B	U	42	4	16		36	2800	113.3	97	1690
42B Four	W	42	4	14.5/16		33.78	3600	91	56	2500
M-50	U	44	4	16		36	3000	115	87.9	1600
W 46	W	46	4	16/18/20/22.5		36.72	3000	127	100	2250
W 52	W	52	4	18		39	3000	135	93	2500

MODEL	MFG	HP	# CYL	MTG CENTERS	REAR MTG CTR	OVERALL LENGTH	RPM	CID	MAX TORQUE	@ RPM
55B Four	W	55	4	16/18.6		35	3000	133.2	110	1500
55A Four	W	55	4	16/18.5		35.2	3600	133.2	93	1920
W 58	W	58	4	18/20/22.5		38.5	3000	154	117.9	2200
W 60	W	60	4	20/22.5		48.5	3000	154	130	2000
63D Four	W	61	4	18.5		38.8	4000	144.4	95	1860
W 70	W	70	4	22.5		38.62	3000	182	148	1800
71C Four	W	71	4	18.5/20/22.5		39.3	3600	154	118	1950
W 80	W	75	4	20/22.5		51.5	2600	230	170	1700
80-N4	W	80	4	22.5		47.2	2500	262	205	1310
82B Four	W	82	4	22.5		38.8	3600	182	146	1890
90A Four	W	90	4	22.5		39.3	3600	210.8	168	1670
W 100	W	100	6	22.5		57	3000	247	195	1800
108C Six	W	108	6	22.5		54.4	3600	247.2	192	1830
110-T4	W	110	4	22.5		47.2	2400	262	296	1240
W 120	W	115	6	20/22.5		61	2600	346		
120-N6	W	120	6	22.5		56.4	2500	396	298	1500
170-T6	W	170	6	22.5		57.5	2500	396	470	1420
5411	U	SEE M15								
5432	U	SEE M40								
5444	U	SEE M50								
M-50A	U	SEE M50								
4-91	W	SEE W30								
4-107	W	SEE W40								
4-154	W	SEE W60								

This information is to be used as a guide only. Specifications are subject to change without notice and Westerbeke is not responsible for any mis-applications.